



TRAILER ORDERING GUIDE

If additional options are required and do not appear on this guide, please note when ordering. This sheet covers basic information.

TO: _____ FROM: _____

COMPANY NAME: _____

DATE: _____ PHONE: _____ FAX: _____

SUSPENSION

(Check all that apply)

SUSPENSION MODEL: TA TI

CAPACITY: 25K 30K

RIDE HEIGHT:
TOP MOUNT (14 THRU 19) Ride Height: _____
LOW MOUNT (9 THRU 12) Ride Height: _____
UNDERSLUNG (6.5 THRU 9) Ride Height: _____
YOKE MOUNT (5.5 THRU 9) Ride Height: _____

FRAME BRACKET: Bolt-On Weld-On Wing
Mounting bolt size: 0.500" Other _____

STRAPS: Yes No Strap over shock: Yes No

BEAM CENTERS: 35" Centers 41" Centers Other *Different options available upon request

CHANNEL: Standard C-Channel Bolt-on C-Channel Customer Supplied
Gussets Other _____

COLLAR: Align-Trac Welded Eccentric

LIFT KIT OPTION: Yes No

COMMENTS _____

AXLES

(Check all that apply)

AXLE TYPE: Straight 6" Drop 6" Inverted Drop

SPINDLE TYPE: N Spindle P Spindle

AXLE TRACK: 71.5" 77.5" Other _____

WALL THICKNESS: 5/8" Nominal 3/4"

TIRE INFLATION: TIREMAAX® CP PSI Other _____

BRAKE SIZE: 12.25" x 7.5" 16.5" x 7" 16.5" x 8.625"

BRAKE CHAMBER SIZE: Service / Spring: 24/24 24/30 30/30
Service Only Type 24 Service Only Type 30

CAM SPLINES: 28 Spline Other _____

COMMENTS _____

TRAILER ORDERING GUIDE

Continued

DRUM BRAKES

(Check all that apply)

SLACK ADJUSTER:	Yes <input type="checkbox"/>	No <input type="checkbox"/>			
BRAKE S-CAM LENGTH:	23.75" (Air Susp.) <input type="checkbox"/>	Bent Tube Axle (Uses special length) <input type="checkbox"/>	Other (17" min. - 27.75" max.) <input type="checkbox"/>		
BRAKE S-CAM ENCLOSURE:	None <input type="checkbox"/>	Cam Tube System <input type="checkbox"/>			
BRAKE ROTATION / POSITION:	BR1 CAMS REAR CHAMBERS DOWN <input type="checkbox"/>	BR2 CAMS FRONT CHAMBERS UP <input type="checkbox"/>			
BRAKE DUST SHIELD:	None <input type="checkbox"/>	Yes <input type="checkbox"/>			
ABS TONE RING:	Yes <input type="checkbox"/>	No <input type="checkbox"/>			
ABS SENSORS INSTALLED:	Yes <input type="checkbox"/>	No <input type="checkbox"/>			
SPINDLE NUT SYSTEM:	Standard <input type="checkbox"/>	Other <input type="checkbox"/>	_____		
HUB MOUNTED:	Hub Pilot <input type="checkbox"/>	Stud Piloted <input type="checkbox"/>			
HUB MATERIAL:	Cast Iron <input type="checkbox"/>	Aluminum <input type="checkbox"/>	ADI <input type="checkbox"/>		
DRUM TYPE:	Cast Iron <input type="checkbox"/>	Other <input type="checkbox"/>	_____		
BOLT PATTERN:	10 Hole 11.25" BC <input type="checkbox"/>	8 Hole 275mm 12.25" x 7.5" Brakes <input type="checkbox"/>			
STUD LENGTH:	Long <input type="checkbox"/>	Short <input type="checkbox"/>	Other <input type="checkbox"/>	_____	
LUBE TYPE:	None <input type="checkbox"/>	Oil SAE 80/90 <input type="checkbox"/>	#2 (Hard) Grease <input type="checkbox"/>	Semi-Fluid Grease <input type="checkbox"/>	
HUBCAP TYPE:	Standard <input type="checkbox"/>	Grease Type <input type="checkbox"/>	TIREMAAX® CP <input type="checkbox"/>	Other <input type="checkbox"/>	_____
COMMENTS	_____				

Contact Watson & Chalin at 972.547.6020 for additional information.



Watson & Chalin
725 E. University Drive, McKinney, Texas 75069
972.547.6020 • 800.445.0736 • Fax 972.542.0097
www.watsonsuspensions.com

