



# TRAILER LIFT AXLE ORDERING GUIDE

If additional options are required and do not appear on this guide, please note when ordering. This sheet covers basic information.

TO: \_\_\_\_\_ FROM: \_\_\_\_\_

COMPANY NAME: \_\_\_\_\_

DATE: \_\_\_\_\_ PHONE: \_\_\_\_\_ FAX: \_\_\_\_\_

TRAILER LIFT AXLES

(Check all that apply)

**SUSPENSION TYPE:** Non-Steer  Steerable

**LIFT AXLE CAPACITY:** 8K  10K  13.5K  20K  25K

**AXLE TRACK:** 71.5"  77.5"  Other  \_\_\_\_\_

**WALL THICKNESS:** 1/2"  5/8" Nominal  3/4"

**BRAKE SIZE:** 12.25" x 7.5"  16.5" x 7"  16.5" x 8.625"

**SPINDLE TYPE:** N Spindle  P Spindle

**ATTACHMENT OPTION:** Bolt-On  Weld-On

**FRAME WIDTH OUTSIDE TO OUTSIDE:** \_\_\_\_\_

or **TRAILER BEAM CENTERS:** \_\_\_\_\_

or **OUTSIDE WIDTH OF FRAME FLANGE:** \_\_\_\_\_

**VEHICLE'S PRIMARY SUSPENSION STYLE:** Air  Mechanical  Spring

**SINGLE OR TANDEM AXLE:** \_\_\_\_\_ Other: \_\_\_\_\_

**GROUND TO BOTTOM OF VEHICLE FRAME HEIGHT AT LIFT AXLE LOCATION:** Loaded \_\_\_\_\_ Unloaded \_\_\_\_\_

**SPECIFIC SIZE OF LIFT AXLE TIRE (255/70R22.5):** \_\_\_\_\_

*Tire size is for ride height calculations, tires and rims are NOT supplied*

**SUSPENSION PLACEMENT:** Pusher (Ahead of primary suspension)  Tag (Behind primary suspension)

**PRE-PLUMBED (if available):** Yes  No

**AIR KIT:** Yes  No  If YES, INSIDE or OUTSIDE CAB \_\_\_\_\_

**AXLE WELDMENT (non-steer only):** Yes  (frame width needed) \_\_\_\_\_ No

**PARKING BRAKES (service brakes are standard):** Yes  No

**LOCKOUT KIT:** Yes  No

**DUST SHIELDS:** Yes  No

**COMMENTS:** \_\_\_\_\_

Contact Watson & Chalin at 972.547.6020 for additional information.



**Watson & Chalin**  
725 E. University Drive, McKinney, Texas 75069  
972.547.6020 • 800.445.0736 • Fax 972.542.0097  
[www.watsonsuspensions.com](http://www.watsonsuspensions.com)

